

CA-5 P

INTRUDER ALARM CONTROL PANEL

The **CA-5** control panel is designed for security of small facilities which do not require future expansion options of the system. The control panel can cooperate with external GSM/GPRS communication modules.

- 5 on board zones
 - support for NC, NO, EOL, 2EOL/NC and 2EOL/NO loop configurations
 - flexible selection of zone function
- 3 outputs (bell output + 2 programmable outputs)
- RS-232 port (TTL) - RJ type socket
- on-board PSTN telephone dialer for reporting, messaging and remote uploading/downloading
- system operation
 - LCD and LED keypads
- system programming
 - local (LCD/LED keypad, PC connected to RS-232 port)
 - remote (PC connected via modem)
- system codes
 - 1 master user code
 - up to 5 user codes
 - 1 service code
- event log with 255 entries
- monitoring using ContactID and other protocols
 - 2 monitoring stations numbers
- advanced telephone tone analysis:
 - TBR-21 compliant tone detection
 - intelligent redial attempts
 - programmable dialing sequence
- built-in 300 bps modem
- autodiagnostic features for basic system components
- on-board switching mode power supply
 - controlled battery charging
 - load battery testing
 - battery deep discharge protection



TECHNISCHE GEGEVENS

Voedingsspanning alarmsysteem (±10%)	12 V DC
Afmetingen print	147 x 70 mm
Bedrijfstemperatuur	-10...+55 °C
Voeding (±15%)	18 V AC, 50-60 Hz
Stand-by verbruik	80 mA
Gewicht	150 g

