

# CA-6 P

## INTRUDER ALARM CONTROL PANEL

The **CA-6** control panel is designed for security of small facilities which do not require future expansion options of the system. The control panel can cooperate with external GSM/GPRS communication modules.

- up to 8 zones
  - support for NC, NO, EOL, 2EOL/NC and 2EOL/NO loop configurations
  - flexible selection of zone function
- additional control input
- 5 programmable outputs
- 2 partitions
- RS-232 port (TTL) - RJ type socket
- on-board PSTN telephone dialer for reporting, messaging and remote uploading/downloading
- system operation
  - LED keypad
  - remote operation by telephone (with optional **MST-1** module)
- system programming
  - local (LED keypad, PC connected to RS-232 port)
  - remote (PC communicating via modem)
- system codes
  - 1 master user code
  - up to 12 user codes
  - 1 service code
- 4 timers
- event log with 255 entries
- event printing feature
- monitoring using ContactID and other protocols
  - 2 monitoring stations numbers
- messaging
  - 4 telephone numbers
  - 1 voice message
  - 2 text messages
- incoming call answering
  - partition state check
  - system operation (with optional **MST-1** module)
- advanced telephone tone analysis:
  - TBR-21 compliant tone detection
  - intelligent redial attempts
  - programmable dialing sequence
- built-in 300 bps modem
- autodiagnostic features for basic system components
- on-board switching mode power supply
  - controlled battery charging
  - load battery testing
  - battery deep discharge protection



### TECHNICAL DATA

Control panels	12 V DC
Board dimensions	142 x 102 mm
Operating temperature range	-10...+55 °C
Main board supply voltage (±15%)	18 V AC, 50-60 Hz

